

MODEL	Stationary Series LT	Wobble Series LT	ATA Series LT	Tournament Stationary 412C, 424C	Tournament Skeet 424C	Tournament Battue 412C, 424C	Tournament Oscill./ATA 424C	Tournament Arm-Rabbit 412 & 424	Tournament Vertical/Teal 412 & 424	Wobble 324	Double Rabbit 324	Double Vert./Teal 324
Target Capacity	270 (2 cases)	270 (2 cases)	270 (2 cases)	400	400	400	400	370	400	300	380	400
Height	39"	39"	41"	38"	38"	33"	41"	44"	44"	39"	50"	50"
Width (Arm Swing)	32"	32"	32"	27"	27"	27"	27"	32"	32"	26"	35"	35"
Length (Arm extend.)	42"	42"	42"	37"	37"	37"	37"	37"	37"	32"	37"	37"
DC Power	12v DC Battery Powered			Series 412 – One 12v AC Deep Cycle Battery Series 424 & 324– Two 12v DC Deep Cycle Battery (in series)								
AC Power	115v AC (optional)			Series 412 – 115v AC Optional on available models Series 424 & 324 – 115v AC Optional (included with Skeet Pair and ATA Traps)								
Interrupter	N/A	Electronic	Electronic	N/A	N/A	N/A	Electronic	N/A	N/A	Electronic	N/A	N/A
Throwing Angles Left & Right	N/A	27° - 60°	27° - 44°	10° Windage	10° Windage	N/A	27°,37°,44° + 10° Windage	N/A	N/A	27°,37°,44° + 10° Windage	N/A	N/A
Throwing Heights Up & Down	0° - 68°	10° - 58°	14° - 25°	0° - 68°	0° - 24°	67° - 112°	14° - 25°	0° - 45°	67° - 112°	0° - 50° 20 settings	0° - 45°	67° - 112°
Side Tilt (Cant)	N/A	N/A	N/A	12° R 24° L	5° (Curl) L or R	15° L	5° (Curl) L or R	N/A	N/A	N/A	N/A	N/A
Target Speed (Distance @ 23° Elev.)	Silver Spring 80 yards + (Standard)			Series 412C & 424C – Adjustable Spring Tension , 120 yards with Red Spring (Standard) approximately 70 yards + Silver Spring (Optional) *N.I.C. Rabbits & Vertical/Teals								

Specifications are subject to change without notice or obligation. E. & O.E.

Revised October 2006